

Datasheet

T35L Flexible Entry Level Thin Client



T35L Flexible entry level thin client

- Based on ARM Cortex A53 Quad core platform
- Support WOL
- Support 10/100/1000 LAN
- Support Chip decoding on RDPFX

T35L specifications

we recommend Linux

Processor	Cortex A53 Quad core 64 bit 1.8 GHz
Available Operating System Protocols	TOS (customized LINUX) RDP 8.1 RemoteFX enabled
RAM (DDR3)	512M
Storage (ROM)	4G EMMC
Port	VGA x 1 HDMI x 1
Resolution	VGA 1920x1080 @60Hz HDMI 1920x1080 @60Hz
Color Depth	32bit true color
LAN	x1 (10/100/1000Mbps Base-T Fast Ethernet, RJ-45)
WLAN	Build-in SDIO onboard WIFI with internal antenna (Optional)
USB 2.0	x5
VESA	Support standard VESA (Optional)
Line-out	x1 (1/8-inch mini-jack, 16-bit stereo)
Device	105mm*105mm*25mm
N.W. G.W.	0.15 kg 0.33 kg
Adapter	5V 2A
Power Consumption	≤5w
Cooling Temperature	Fan-less Convection 20% to 80 % condensing, 10% to 95% non-condensing

For more info:

tita-tech.com

E-mail:

Enquiry@tita-tech.com

