

Datasheet

TC120v3.0 Powerful Entry Level Endpoint Device



TC120v3.0 Entry level Endpoint Smart Device

- Based on Intel Quad core Cherry Trail platform.
- 10/100/1000 Ethernet
- Supports Windows 10 pro / Ubuntu 16.04 / TOS (TITA OS for thin client)
- Supports PXE
- Supports auto power on

TC120v3.0 specifications

we recommend windows / TOS

Processor Burst Frequency	Intel Cherry Tail Z8350 1.44 GHz Quad core up to 1.92 GHz
Available Operating System	Windows 10 Pro / LINUX (Ubuntu 16.04) / TOS (TITA zero client OS)
RAM (DDR3)	4G (2G Optional)
Storage (ROM)	64G EMMC (8G / 32G Optional)
Port	VGA x 1 HDMI x 1
Resolution	VGA 1920x1200 HDMI 1920x1080 Dual display via HDMI + VGA (Extended)
Color Depth	32bit true color
LAN	x1 (10/100/1000 Mbps Base-T Fast Ethernet, RJ-45)
WLAN BT	WI-FI IEEE 802.11a/b/g/n, 2.4G+5.0G (build-in) 4.0
USB 2.0 USB 3.0	X3 x1
Line-out	x1 (1/8-inch mini-jack, 16-bit stereo)
Device	119.6mm*119.6mm*25mm
N.W. G.W.	0.25 kg 0.65 kg
Adapter	12V/1.5A DC
Power Consumption	Standby mode: 3.0w, Full load mode: 8.0w
Other features	Auto Power on PXE
Cooling	Fan-less Convection

For more info:

tita-tech.com

E-mail:

Enquiry@tita-tech.com



Specification is subject to be modified without notification.